

Dock Levelers



Type	Dock Levelers	PL. indicate your requirement
Make	NIHVA	
Capacity in KG	6000/9000/10000/12000/15000	
Platform Width in MM	2030	
Platform Length in MM	2720	
Lip Width in MM	2030	
Lip Length in MM	400	
Working Length (Including Lip) in MM	Direct by electric Motor	
Overall Length in MM	2720	
Overall Width in MM	2030	
Shut Height in MM	485	
Working Range UP/Down in MM	(+) 300 / (-) 250	
Loading Platform Height from Road in MM	1250	
Dock Operation Mode	AC Power Pack Hydraulically Operated	
Lip Operation Mode	Hydraulically Operated	
Operation Control	Through Panel	
Power Pack	Hydraulic	
Drive Type	Direct by electric Motor	
Motor Ratings HP / Make	1HP/Crompton	
Pump Design Flow (LPM)	2.5	
Pump Type	Gear	
Safety Valve Set Pressure (Kg/Sq. Cm)	120	
Volume of Oil Receiver (Liter)	7	
No. Of Deck Cylinder	1 / 2 (optional)	
No. Of Lip Cylinder	1	
Power Supply	3 Phase	
Maximum Gradient	1:10	
Clear Pit Dimensions (W x L x D)	2080 X 2780 X 485	

We Make Possible



Visit US: www.nihva.com

☎ 91 8551091333 📞 +91 20 66304033

Email: marketing@nihva.com

MM		
Service Weight in Kg (Approx.)	900	
Colour	Golden Yellow	