

NIHVA Double Wall Rolling Shutter

Clear Opening dimension	: (w) -- x (h) -- :
Opening Direction	: Vertical - from bottom to Top
Mounting Location area	: Only Inside area
Mounting Surface	: Side Brackets: Optional = On Concrete / Steel & Side Guides : Optional = On Concrete/Steel / Masonry
Opening/Closing Speed	: 0.1 m/sec
Wind Resistance	: 120 Km/hrs.
Slats material	: insulated pre coated Galvanized steel (PU foam)
Slat size	: 95mm x 19mm with PU filled inside
Curtain Panel	: The panel made of 1.0mm thick CRCA steel
Curtain Profile	: Corrugation
Slat (made in Option)	: Optional - German slats / China slats
Bottom Profile	: 125mm x 15mm with extra angle support. (Optional - Rubber Bottom Seal)
Side Guide Profile	: M.S." U" Shaped profile 125 x 40mm x 3 mm thick (as per the opening width dimension)
Roller Shaft	: MS Plate 3 mm to 10 mm thick
Side Brackets	: MS Plate 3 mm to 10 mm thick
Hood Cover	: GI Thick 0.8mm with 25x25x3mm angle stiffener
<u>Surface finish</u>	
Painting	: Powder coated – Off white color
Vision Windows	: With Vision Window / without Vision Window

We Make Possible



Visit Us: www.nihva.com

☎ 91 8551091333 📞 +91 20 66304033

Email: marketing@nihva.com

Automation

Control Type : Optional = Dead man / Pulse Control

Drive Unit & Mounting Type:

Option 1) Electric Motor (Imported German Make) (Single Phase/Three Phase) - Direct Mounting on Shaft

Option 2) Electric Motor (Imported China make) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement

Emergency Operation:

Option = Manual Hand Driven / Chain Wheel Drive

Operating Mode:

Option = Push Button from inside / or do you need Outside also

Option = Push Button / Key Switch From Outside

Integration optional:

Option = need to interlock or integrate with other door or machine or Equipment

Accessories: Option = Flashing Light / Safety Photocell / Remote Control

Installation Constraint any:

Need to be check = Space requirements + sub structure scope of work + Mounting access + Access in the event of power cut + clear opening dimensions

**** Option = need to select or specify your requirement by choosing Option, so clear communication will happen between us.**