

Product:**NIHVA Motorized Sliding Gate**

Clear Opening gate dimension: Clear Opening gate dimension (w) -- x (h) –

Type of Gate : Track Sliding gate type / Cantilever type/Telescopic type

Opening Direction : Horizontal - from left to right or reverse
Max no of leafs : **Single** / Double leaf / Multiple Leaf's (left hand & right hand)
Mounting Surface : Bottom Rail:RCC & Columns:RCC
Design Pattern : Standard Tubular Design Pattern
Outer Frame Tube : Outer Frame Tube Sizes

Internal Vertical Tube Sizes:

Above 8.0 m Width: 91.5 x 91.5 x 3.2 mm Up to 8.0 m Width : 32 x 32 x 2.0 mm
Above 8.0 m Width: 40 x 40 x 2.0mm Placed at 150 mm c/c

Bottom Rail on ground: dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams

Bottom Rollers: Heavy Duty Bottom Wheel With both side Bearings (chrome plated)

Full Height Column sizes : Up to 8.0 m Width : 72 x 72 x x 3.2 mm
Above 8.0 m Width: 91.5 x 91.5 x 3.2 mm

Guide Rollers supporter during Gate movement: Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate

Painting: 2 Coats of EPOXY polyamide based enamel finish of approved colour RAL 7015

Options Available: Material options / Various Design options / any other special req.

Control Type: Advance control > Electromechanical microswitches (inductive in the PROX version) that control the end stroke. > Incorporated two-channel rolling code radio receiver. > Control unit with self-learning and self- diagnostic functions

Drive Unit & Mounting Type: Made in Italy - non reversible gear motor

Emergency: Manual after turn the switch

Operating Switch: Push Button from inside Optional push Button/Key Switch From Outside

Metal Rack: zinc plated metal rack

Accessories: Flashing Light Door line Safety Photocell Remote Control with receiver (range - 3m)

Installation Constraint If any: need to be check = space requirements + substructure + Mounting access + Access in the event of power cut

We Make Possible



Visit Us: www.nihva.com

☎ 091 8551091333 📞 +91 20 66304033

Email: marketing@nihva.com