

Mobile Ramp



Type	Mobile Ramp	PL. indicate your requirement
Make	NIHVA	
Capacity in KG	6000/9000/10000/13000	
Platform Width in MM	Customized	
Platform Length in MM	Customized	
Lip Width in MM	Customized	
Lip Length in MM	Customized	
Shut Height in MM	Customized	
Working Range UP/Down in MM	(+) 300 / (-) 250	
Loading Platform Height from Road in MM	1250	
Dock Operation Mode	AC Power Pack Hydraulically Operated	
Lip Operation Mode	Hydraulically Operated	
Operation Control	Through Panel	
Power Pack	Hydraulic	
Drive Type	Direct by electric Motor	
Motor Make	Crompton	
Pump Design Flow (LPM)	2.5	
Pump Type	Gear	
Safety Valve Set Pressure (Kg/Sq. Cm)	120	
Volume of Oil Receiver (Liter)	7	
No. Of Deck Cylinder	1	
No. Of Lip Cylinder	1	
Power Supply	3 Phase	
Color	Golden Yellow	
Railing Type	2 side	
Railing Height in MM	350	
No. of Pendant	Optional	
Resting Pads	Provided	
No. of Fixed wheels	2	
No. of Castor Wheels	2	

We Make Possible



Visit US: www.nihva.com

☎ 91 8551008333 📞 +91 20 66304033

Email: marketing@nihva.com

We Make Possible



Visit US: www.nihva.com

📞 +91 20 66304033

Email: marketing@nihva.com